

10/29/99

JCS685 U.S. - PTO

13. ☐ Attached: _____ (No.) Verified Statement(s) establishing "small entity" status under Rules 9 & 27.

14. **DOMESTIC/INTERNATIONAL** priority is claimed under 35 USC 119(e)/120/365(c) based on the following provisional, nonprovisional and/or PCT international application(s):

Application No.	Filing Date	Application No.	Filing Date
(1)		(4)	
(2)		(5)	
(3)		(6)	

JCS685 U.S. - PTO
09/29/99
10/29/99

15. ☐ This application is being filed under Rule 53(b)(2) since an inventor is named in the enclosed Declaration who was not named in the prior application.

16. ☒ Attached: IDS Letter Citing Application(s) and PTO-1449

17. ☐ Preliminary Amendment:

THE FOLLOWING FILING FEE IS BASED ON CLAIMS AS FILED LESS ANY ABOVE CANCELLED

				Large/Small Entity		Fee Code
18. Basic Filing Fee				\$760/\$380	\$760	101/201
19. Total Effective Claims	15	minus 20 =	*0	x \$18/\$9 =	+ 0	103/203
20. Independent Claims	2	minus 3 =	*0	x \$78/\$39 =	+ 0	102/202
*If answer is zero or less, enter "0"						
21. If <u>any proper</u> multiple dependent claim (ignore improper) is present, add (Leave this line blank if this is a reissue application)				+ \$260/\$130	+ 0	104/204
22. TOTAL FILING FEE ENCLOSED =					\$760	
23. If "non-English" box 2 is X'd, add Rule 17(k) processing fee				+ \$130	+ 0	139
24. If "assignment" box 6 is X'd, add recording fee				+ \$40	+ 40	581
25. <input type="checkbox"/> Attached is a Petition/Fee under Rule No.				+ \$130	+ 0	122
26. TOTAL FEE ENCLOSED =					\$800	

Our Deposit Account No. 03-3975

Our Order No. 30954 264103
C# M#

CHARGE STATEMENT: The Commissioner is hereby authorized to charge any fee specifically authorized hereafter, or any missing or insufficient fee(s) filed, or asserted to be filed, or which should have been filed herewith or concerning any paper filed hereafter, and which may be required under Rules 16-18 (missing or insufficient fee only) now or hereafter relative to this application and the resulting Official document under Rule 20, or credit any overpayment, to our Account/Order Nos. shown above for which purpose a duplicate copy of this sheet is attached.

This **CHARGE STATEMENT** does not authorize charge of the issue fee until/unless an issue fee transmittal form is filed.

Pillsbury Madison & Sutro LLP
Intellectual Property Group

1100 New York Avenue, N.W.
Ninth Floor, East Tower
Washington, D.C. 20005-3918
Tel: (202) 861-3000
GLK/nlh

By Atty: G. Lloyd Knight

Reg. No. 17698

Sig:

G. Lloyd Knight

Fax: (202) 822-0944

Tel: (202) 861-3090

NOTE: File in duplicate with 2 post card receipts (PAT-103) & attachments

APPLICATION UNDER UNITED STATES PATENT LAWS

Invention: LEAD-WIRE ARRANGEMENT OF VEHICLE AC GENERATOR

Inventor(s): SHICHIHYO, Akiya

Pillsbury Madison & Sutro LLP
Intellectual Property Group
1100 New York Avenue, N.W.
Ninth Floor, East Tower
Washington, D.C. 20005-3918
Attorneys
Telephone: (202) 861-3000

This is a:

- ☐ Provisional Application
- ☒ Regular Utility Application
- ☐ Continuing Application
- ☐ PCT National Phase Application
- ☐ Design Application
- ☐ Reissue Application
- ☐ Plant Application
- ☐ Substitute Specification
Sub. Spec. filed _____
in App. No. _____ / _____
- ☐ Marked Up Specification re
Sub. Spec. filed _____
in App. No. _____ / _____

SPECIFICATION

LEAD-WIRE ARRANGEMENT OF VEHICLE AC GENERATOR

CROSS REFERENCE TO RELATED APPLICATION

The present application is based on and claims priority
5 from Japanese Patent Application Hei 11-28192 filed on February
5, 1999, the contents of which are incorporated herein by
reference.

BACKGROUND OF THE INVENTION

10 1. Field of the Invention

The present invention relates to an ac generator for
a vehicle, and particularly to a stator lead-wire arrangement
of an ac generator.

2. Description of the Related Art

15 JP-A-4-165949 and JP-A-4-26345 disclose ac generators
which have a frame, a stator, a rotor, a rectifier unit, a
brush unit, and a voltage regulator. The stator has a three-
phase stator winding and accommodated inside the frame, and the
rectifier unit is fixed outside the frame. In this type of ac
20 generator, it is necessary to have a plurality of lead-wire-
holes at a wall of the frame for a plurality of lead wires
extending from the stator winding through the frame to be
connected to the rectifier unit.

As the number of holes increases, the wall becomes more
25 uneven, thereby causing a loud fan noise. Moreover, because the
number of insulators to be inserted into the holes increases,
the production cost increases.

SUMMARY OF THE INVENTION

A main object of the invention is to provide an improved lead-wire arrangement of an ac generator for a vehicle.

5 Another object of the invention is to provide an ac generator which has an inexpensive structure for suppressing a fan noise.

10 According to a preferred embodiment of the invention, an ac generator including a stator having a multi-phase stator winding, a rectifier unit, a frame having a wall supporting the stator at one side thereof and the rectifier unit at the other side. The wall has a minimal number of lead-wire-holes for the output lead wires. Terminal members may be disposed in the lead-wire-holes for holding the output lead wires.

15 BRIEF DESCRIPTION OF THE DRAWINGS

20 Other objects, features and characteristics of the present invention as well as the functions of related parts of the present invention will become clear from a study of the following detailed description, the appended claims and the drawings. In the drawings:

Fig. 1 is a partially cross-sectional side view of an ac generator for a vehicle according to a preferred embodiment of the invention;

25 Fig. 2 is a schematic circuit diagram of the ac generator shown in Fig. 1;

Fig. 3 is a plan view illustrating a stator with a

stator winding;

Fig. 4 is a schematic plan view of a rectifier unit of the ac generator;

Fig. 5 is a fragmentary front view illustrating a connection unit of the rectifier unit;

Fig. 6 is a fragmentary side view illustrating the connection unit of the rectifier unit;

Fig. 7 is a fragmentary cross-sectional view illustrating the connection unit;

Fig. 8 is a view illustrating the connection unit viewed from position P in Fig. 7;

Fig. 9 is a plan view of a rear frame of the ac generator;

Fig. 10 is a variation of the stator shown in Fig. 3.

Fig. 11 is a fragmentary side view illustrating a variation of the stator; and

Fig. 12 is a fragmentary side view illustrating a variation of the stator.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in Fig. 1, ac generator 1 for a vehicle according to a preferred embodiment of the invention includes stator 2 having 96 slots at the inner periphery thereof, rotor 3 having sixteen claw poles, frame 4, rectifier unit 7, pulley 20 and others. The ac generator provides dc output power, when pulley 20 is rotated by an engine through a V-belt (not shown) in a well-known manner.

Stator 2 has stator core 22 and stator winding 23 with magnet wires disposed in the stator's slots. Stator winding 23 is composed of first three-phase star-connected winding 23a and second three-phase star-connected winding 23b. They are shifted from each other by an electric angle of 30° or one slot-pitch. First winding 23a has three phase-windings X, Y and Z which are connected with each other at their one ends to form first neutral point N1, and second winding 23b has three phase-windings U, V and W which are connected with each other at their one ends to form second neutral point N2, as shown in Fig. 2. Each phase-winding has eight two-turn coils disposed in the slots at equal intervals and four wires are disposed in each slot.

Rotor 3 has pole core 31, field coil 32, mixed-flow-type front cooling fan 35, and centrifugal rear cooling fan 36. Pole core 31 has eight claw poles 33 alternately interleaved with each other to form an eight-pole rotor. Field coil 32 is enclosed by claw poles 33 in a well-known manner.

Frame 4 supports stator 2 and rotor 3 so that rotor 3 can rotate with rotor shaft 34 inside stator 2. Frame 4 is composed of front frame 4a and rear frame 4b, which are fastened by four bolts 41. Frame 4 has air-discharge windows 42 at the portions thereof opposite the coil-ends of stator winding 23 and air-intake windows at the central portions thereof.

Voltage regulator 6, rectifier unit 7, brush unit 8 are respectively fixed to the rear wall surface of rear frame 4b

and covered by rear cover 5.

As shown in Fig. 2, rectifier unit 7 is composed of a pair of full-wave three-phase bridge circuits 7a and 7b, which are respectively connected to stator winding 2 via output lead wires X1, Y1, and Z1 respectively extending from three phase-windings X, Y, Z of first winding 23a at input portions 71a, 72a, and 73a and via output lead wires U1, V1, and W1 respectively extending from three phase-windings U, V and W of second winding 23b at input portions 71b, 72b and 73b. First neutral point N1 is formed by neutral lead wires X2, Y2, and Z2 respectively extending from three phase-windings X, Y, Z, and the second neutral point N2 is formed by neutral lead wires U2, V2, and W2 respectively extending from three phase-windings U, V, and W.

As shown in Fig. 3, output lead wires X1 and Y1 of first winding 23a respectively extend from portions close to each other to form a first bundle of output lead wires, while output lead wire Z1 of the same winding extends from a portion remote from the former portions. Neutral lead wires X2, Y2 and Z2 respectively extend from portions close to the portions from which output lead wires X1, Y1, and Z1 extend. Neutral lead wire Z2 further extends clockwise along the axial end surface of the circumferential coil-ends to the portions from where the other neutral lead wires X2 and Y2 of first winding 23A extend. Three neutral lead wires X2, Y2 and Z2 of first winding are welded or soldered to each other to form first neutral point N1.

Output lead wires V1 and W1 of second winding 23b respectively extend from portions close to each other to form a second bundle of output lead wires, while output lead wire U1 of the same winding extends from a portion remote from the former portions but close to output lead wire Z1 to form a third bundle of output lead wires. Neutral lead wires U2, V2 and W2 respectively extend from portions close to the portions from which output lead wires U1, V1, and W1 extend. Neutral lead wire U2 further extends counter-clockwise along the axial end surface of the circumferential coil-ends to the portions from where the other neutral lead wires V2 and W2 of second winding 23b extend. Three neutral lead wires U2, V2 and W2 of second winding 23b are welded or soldered to each other to form second neutral point N2. Thus, two neutral points N1 and N2 can be formed at the coil-end portions remote from each other. This simplifies the connection work.

As shown in Fig. 4, rectifier unit 7 includes arc-shaped negative cooling fin 74 holding six negative-side diodes 751-756, arc-shaped positive cooling fin 76 holding six positive-side diodes 771-776, and connection unit 78 disposed between negative cooling fin 74 and positive cooling fin 76. Connection unit 78 spaces and insulates the cooling fins from each other, and also connects each diode to respectively form full-wave three-phase bridge circuits 7a and 7b. Bridge circuit 7a is composed of three negative-side diodes 751-753 and three positive-side diodes 771-773 which are disposed at the left section of rectifier unit 7, and bridge circuit 7b is composed

of three negative-side diodes 754-756 and three positive-side diodes 774-775 which are disposed at the right section of rectifier unit 7.

Connection unit 78 has three terminal members 781, 782, and 783 spaced apart from one another along the arc-shaped periphery thereof. They connect output lead wires X1, Y1, Z1, U1, V1, and W1 to respective rectifier bridge circuits 7a, and 7b.

First terminal member 781 is located near negative diodes 751, 752 and positive diodes 771, 772 and near the first bundle of output lead wires X1 and Y1; second terminal members 782 is located near negative diodes 755, 756 and positive diodes 775, 776 and near the second bundle of output lead wires V1 and W1; and the third terminal members 783 is located near negative-side diodes 753, 754 and positive-side diodes 773, 774 and near the third bundle of output lead wires Z1 and U1. Thus, three circuit groups are disposed regularly in the circumferential direction.

As shown in Figs. 5 and 6, first terminal member 781 has a pair of terminals 71a and 72a and a columnar terminal member extending in the axial direction. The columnar terminal member has a pair of bell-bottomed concavities 82 therein to respectively hold the output lead wires X1 and Y1 and introduces them to the pair of terminals 71a, 72a. Concavity 82 becomes gradually wider at the open end so that the lead wires can be easily inserted therein. Terminal 71a connects output lead wire X1 to the junction of negative-side diode 751

and positive side diode 771, and terminal 72a connects output lead wire Y1 to the junction of negative-side diode 752 and positive-side diode 772. The connection is carried out by soldering, welding or bolt-fastening.

5 As shown in Figs. 7, 8, and 9, first terminal member 781 is inserted into one of three lead-wire-holes 44 formed coaxially at the end wall of rear frame 4b. Other two lead-wire-holes 44, are also formed at the portions of rear frame 4a to correspond to second and third terminal members 782 and 783. In the preferred embodiment, the number of lead-wire-holes 10 44 equals to the number of phases (e.g. three).

15 If neutral diode circuits are connected to the neutral points N1 and N2 in a known manner, one more lead-wire-hole for another terminal member is necessary to hold two more output lead wires. Thus, the number of lead-wire-holes are minimized so that irregularities of the rear frame's wall surface opposite rear cooling fan 36 can be minimized. This prevents the fan noise effectively. The number of the lead-wire holes does not change even if the star-connected three-phase winding 20 is changed to Δ -connected three-phase windings.

25 Second terminal member 782 for output lead wires V1 and W1 and third terminal member 783 for output lead wires Z1 and U1 are the same in structure.

30 A variation of stator winding 2 according to the preferred embodiment is described with reference to Fig. 10.

35 Output lead wire Z1 of first winding 23a and output lead wire W1 respectively extend from portions close to each

other to form a first bundle of output lead wires to be held in first terminal member 781; output lead wire Y1 of first winding 23a and output lead wire V1 respectively extend from portions close to each other to form a second bundle of output lead wires to be held in second terminal member 782; and output lead wire X1 of first winding 23a and output lead wire U1 respectively extend from portions close to each other to form a third bundle of output lead wires to be held in third terminal member 783. The third bundle of output lead wires is located at the middle between the first and second bundles of output lead wires. In other words, the third bundle is about 90° in angle spaced apart from the first bundle and from the second bundle.

Neutral lead wires X2, Y2 and Z2 respectively extend from portions in the vicinity where output lead wires X1, Y1, and Z1 extend. Neutral lead wire Z2 further extends counter-clockwise along the axial end surface of the circumferential coil-ends to the portion close to the third bundle of output lead wires, from where the other neutral lead wires X2 and Y2 of second winding 23b extend. Neutral lead wire Y2 further extends clockwise along the axial end surface of the circumferential coil-ends to the other neutral lead wires X2 and Y2 of first winding 23a extend. Three neutral lead wires X2, Y2 and Z2 of first winding 23a are welded or soldered to each other to form first neutral point N1.

Because first winding 23a and second winding 23b are shifted from each other by electric angle 30° , the output

voltages of the output lead wires held in each terminal member have a small phase difference therebetween. Therefore, even if the output lead wires of the bundle are short-circuited to each other, at least a portion of the output power can be provided.

5 Neutral lead wires U2, V2 and W2 respectively extend in close proximity to output lead wires U1, V1, and W1. Neutral lead wire V2 further extends counter-clockwise along the axial end surface of the circumferential coil-ends, and neutral lead wire W2 further extends clockwise along the axial end surface of the circumferential coil-ends, so that they
10 meet at neutral lead wire U2. Three neutral lead wires U2, V2 and W2 of second winding 23b are welded or soldered to each other to form second neutral point N2. Thus, two neutral points N1 and N2 can be formed at the coil-end portions remote
15 from each other.

 It is also possible to gather two output lead wires other than those described above to form a bundle of output lead wires to be held in a terminal member in the similar manner.

20 In Fig. 11, two output lead wires Z1 and U1 extend from portions relatively remote from each other.

 In Fig. 12, two output lead wires Z1 and U1 shown in Fig. 11 are formed in a crank-shape to be substituted for the stator shown in Fig. 1. The crank-shape can prevent deformation
25 of the output lead wires.

 The terminal members can be separated from the connection unit.

In the foregoing description of the present invention, the invention has been disclosed with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made to the specific
5 embodiments of the present invention without departing from the broader spirit and scope of the invention as set forth in the appended claims. Accordingly, the description of the present invention in this document is to be regarded in an illustrative, rather than restrictive, sense.

What is claimed is:

1. An ac generator for a vehicle comprising:
 - a rotor having a shaft;
 - a stator having a multi-phase stator winding which has output lead wires for respective phase voltages;
 - a rectifier unit having input terminals respectively connected to said output lead wires; and
 - a frame having a wall supporting said stator at one side thereof and said rectifier unit at the other side, said wall having lead-wire-holes for at least two of said output lead wires to be respectively connected to said input terminals.
2. The ac generator as claimed in claim 1, further comprising a cooling fan fixed to one end of said rotor near said rectifier unit.
3. The ac generator as claimed in claim 1, further comprising a terminal member disposed in said lead-wire-holes for holding said output lead wires.
4. The ac generator as claimed in claim 1, wherein said multi-phase stator winding comprises a plurality of three-phase windings which are different in phase.
5. The ac generator as claimed in claim 4, wherein said

rectifier unit comprises a plurality of three-phase full-wave rectifiers for said plurality of three-phase windings.

6. The ac generator as claimed in claim 5, wherein
said rectifier unit comprises a common positive cooling fin and a common negative cooling fin.

7. The ac generator as claimed in claim 4, wherein
said three-phase windings are disposed in said stator to generate three-phase voltages which are close in phase to each other,

said wall has three lead-wire-holes each of which has a bundle of said output lead wires respectively extending from said pair of three-phase windings, and

said output lead wires in said bundle are close to each other in phase.

8. The ac generator as claimed in claim 4 wherein
said stator winding comprises a first star-connected three-phase winding and a second star-connected three-phase winding.

9. An ac generator for a vehicle comprising:
a multi-poled rotor;
a stator having a multi-phase stator winding which has output lead wires for multi-phase output voltages, respective two of said output lead wires forming a plurality of bundles;

a full-wave rectifier unit having input terminals disposed to correspond to said bundles and respectively connected to said output lead wires; and

a frame having a wall supporting said stator at one side thereof and said rectifier unit at the other side, said wall having lead-wire-holes disposed to correspond to said bundles.

10. The ac generator as claimed in claim 9, further comprising terminal members respectively disposed in said lead-wire-holes for insulating said bundles from each other.

11. The ac generator as claimed in claim 10, wherein said multi-phase stator winding comprises a plurality of three-phase windings which are different in phase.

12. The ac generator as claimed in claim 11, wherein said rectifier unit comprises a plurality of three-phase full-wave rectifiers for said pair of three-phase windings.

13. The ac generator as claimed in claim 12, wherein said rectifier unit comprises a common positive cooling fin and a common negative cooling fin.

14. The ac generator as claimed in claim 13, wherein said three-phase windings are disposed in said stator to generate three-phase voltages which are close in phase to

each other; and

each of said bundles has a pair of said output lead wires which are close in phase to each other.

15. The ac generator as claimed in claim 14 wherein

each of said three-phase windings comprises a star-connected phase-winding.

ABSTRACT

An ac generator for a vehicle includes a multi-poled rotor, a stator having a multi-phase stator winding which has output lead wires, a full-wave rectifier unit, and a frame having a wall supporting the stator at one side thereof and the rectifier unit at the other side. The output lead wires are grouped to form a plurality of bundles. The wall has lead-wire-holes formed to correspond to the bundles. The rectifier unit has input terminals disposed to correspond to the bundles and respectively connected to the output lead wires.

FIG. 1




FIG. 2




FIG. 4




FIG. 3




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG.10




FIG.11





FIG.12



52145-012

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the INVENTION ENTITLED LEAD-WIRE ARRANGEMENT OF VEHICLE AC GENERATOR

the specification of which (CHECK applicable BOX(ES))

X -> [x] is attached hereto.

BOX(ES) -> [] was filed on _____ as U.S. Application No. 0. / _____

-> [] was filed as PCT International Application No. PCT/ _____ on _____

-> -> and (if U.S. or PCT application amended) was amended on _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56. I hereby claim foreign priority benefits under 35 U.S.C. 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate filed by me or my assignee disclosing the subject matter claimed in this application and having a filing date (1) before that of the application on which priority is claimed, or (2) if no priority claimed, before the filing date of this application:

PRIOR FOREIGN APPLICATION(S)			Date first Laid- open or Published	Date Patented or Granted	Priority Claimed Yes No
Number	Country	Day/MONTH/Year Filed			
11-28192	Japan	5 / February / 1999			x

I hereby claim domestic priority benefit under 35 U.S.C. 119/120/365 of the indicated United States applications listed below and PCT international applications listed above or below and, if this is a continuation-in-part (CIP) application, insofar as the subject matter disclosed and claimed in this application is in addition to that disclosed in such prior applications, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56 which became available between the filing date of each such prior application and the national or PCT international filing date of this application:

PRIOR U.S. PROVISIONAL, NONPROVISIONAL AND/OR PCT APPLICATION(S)			Status pending, abandoned, patented	Priority Claimed Yes No
Application No. (series code/serial no.)	Day/MONTH/Year Filed			

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

And I hereby appoint Pillsbury Madison & Sutro LLP, Intellectual Property Group, 1100 New York Avenue, N.W., Ninth Floor, East Tower, Washington, D.C. 20005-3918, telephone number (202) 861-3000 (to whom all communications are to be directed), and the below-named persons (of the same address) individually and collectively my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent, and I hereby authorize them to delete names/numbers below of persons no longer with their firm and to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/ organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct the above Firm and/or a below attorney in writing to the contrary.

Paul N. Kokulis	16773	Donald J. Bird	25323	Lynn E. Eccleston	35861	Richard H. Zaitlen	27248
Raymond F. Lippitt	17519	Peter W. Gowdey	25872	David A. Jakopin	32995	Roger R. Wise	31204
G. Lloyd Knight	17698	Dale S. Lazar	28872	Mark G. Paulson	30793	Jay M. Finkelstein	21082
Carl G. Love	18781	Glenn J. Perry	28458	Timothy J. Klima	34852	Anita M. Kirkpatrick	32617
Edgar H. Martin	26522	Kendrew H. Colton	30368	Stephen C. Glazier	31361	Michael R. Dzwonczyk	36787
Kevin E. Joyce	20508	Paul E. White, Jr.	32011	Paul F. McQuade	31542	W. Patrick Bengtsson	32456
George M. Sirilla	18221	G. Paul Edgell	24238	Ruth N. Morduch	31044		

1. INVENTOR'S SIGNATURE: Akiya Shichijyo Date September 6, 1999
 Inventor's Name (typed) Akiya Shichijyo Japan
 First Middle Initial Family Name Country of Citizenship
 Residence (City) Ama-gun Japan
 Post Office Address (Include Zip Code) c/o DENSO CORPORATION, 1-1 Showa-cho Kariya-city Aichi-pref. 448-8661 Japan

2. INVENTOR'S SIGNATURE: _____ Date _____
 Inventor's Name (typed) _____
 First Middle Initial Family Name Country of Citizenship
 Residence (City) _____
 Post Office Address (Include Zip Code) _____

3. INVENTOR'S SIGNATURE: _____ Date _____
 Inventor's Name (typed) _____
 First Middle Initial Family Name Country of Citizenship
 Residence (City) _____
 Post Office Address (Include Zip Code) _____

(FOR ADDITIONAL INVENTORS, check box [] and attach sheet (PAT-116.2) for same information for each re signature, name, date, citizenship, residence and address.)